

NEMA Locking Cable Chart for PDU Cables

Part Number	Receptacle	Service			Breaker		Wire		Conduit Inches
		Volts	AMP	Phase	P	A	Quantity	Size	
L515R1*	4710	120	15	1	1	15	3	12 AWG	0.5
L515R2*	4700	120	15	1	1	15	3	12 AWG	0.5
L520R1*	2310	120	20	1	1	20	3	12 AWG	0.5
L530R1*	2610)	120	30	1	1	30	3	10 AWG	0.5
L615R1*	4560	208	15	1	2	15	3	12 AWG	0.5
L615R2*	4550	208	15	1	2	15	3	12 AWG	0.5
L620R1*	2320	208	20	1	2	20	3	12 AWG	0.5
L630R1*	2620	208	30	1	2	30	3	10 AWG	0.5
L715R1	4760	208	15	1	2	15	3	12 AWG	0.5
L1420R1*	2410	120/208	20	1	2	20	4	12 AWG	0.5
L1430R1*	2710	120/208	30	1	1	30	4	10 AWG	0.5
L1520R1*	2420	208	20	3	3	20	4	12 AWG	0.5
L1530R1*	2720	208	30	3	3	30	4	10 AWG	0.5
L2120R1*	2510	208	20	3	3	20	5	12 AWG	0.5
L2130R1*	2810	208	30	3	3	30	5	10 AWG	0.5

***Available with isolated ground.** All NEMA Type cable assemblies are available in daisy-chain configurations.